



Decofilt



Technical Parameters

No.	Parameter	Description
1.	Fabric technical name:	Decofilt 21 415000
2.	Type of manufacture / Structure:	needle-punch / felt
3.	Type of raw material:	100% PES - polyester
3.	Secondary backing	foam
4.	Fabric weight:	1450 g / 2,7 mm , 1605 g / 3,2 mm
5.	Maximum print width	5 m
6.	Stroll test	≤ 2 kV
7.	Impact sound reduction	ΔL_w ca. 24 dB
8.	Thermal conductivity	Ca. 0,10 m ² K/W
9.	Flammability	C _{fl} – sI EN 13501-1
10.	Knit textile retardant	BN-SI

Decofilt

Decofilt 2I is a needle-punched polyester felt with foam backing, designed for decorative and functional applications. It is commonly used for advertising purposes, such as printed flooring mats, providing a durable and soft surface with good impact sound reduction.

Thanks to its wide format and flame resistance, Decofilt 2I is suitable for various indoor commercial and residential applications. Its combination of flexibility and stability makes it ideal for temporary installations, exhibitions, and promotional displays.

Printing technology:

	Direct sublimation	Transfer sublimation	UV
Printing compatibility	✗	✓	✗

Compatible product



Mat

Standard Finishing



Standard
Double Stitching




Tunnel




Band (Sewn-On)



Band (On Back)



Edge Reinforcement
+ Eyelet



Keder 8,5 Mm



Do you need any advice?

Contact with our Customer Service! [Click here](#)